

Home ■ Produits ■ Séparation et traitement des sables ■ Procédés de traitement des sables ■
HUBER Grit Treatment Process RoSF 5-VW(S)



- Loss on ignition of the grit/gravel fraction < 3%
- Coarse material separation size of 10 mm
- Reduced disposal costs

Consisting of:

- Acceptance station with vertical dosing screw
- Coarse material separation
- Grit classifying and washing
- Optional conditioning of circulation water

- Reduction of organics in the grit/gravel fraction to < 3% loss on ignition
- Reduction in disposal volumes and costs

- Maximum minerals yield
- > 95% capture rate of 0.20 – 0.25 mm diameter grit particles
- Coarse material separation size of 10 mm
- Allows for reuse of the mineral material
- Manufactured entirely of stainless steel for maximum corrosion resistance

 [Brochure: HUBER Grit Treatment System RoSF 5VW\(S\) \(anglais\)](#) [pdf, 355 KB]

- Les stations d'épuration misent de plus en plus sur la technique HUBER pour le traitement de matériaux externes
- [HUBER Grit Treatment Process RoSF 5-HW\(S\)](#)

Winkelstrasse 12
CH-6048 Horw

Telefon +41 (0)41 349 68 68
Telefax +41 (0)41 349 68 78

E-mail: info@picatech.ch
www.picatech.ch

MWST Nr. 156 391