

[Home](#) ■ [Products](#) ■ [Grit Separation and Treatment](#) ■ [Longitudinal Grit Traps](#)

## Longitudinal Grit Traps

For the reason of operating reliability of wastewater treatment plants it is necessary to separate the grit transported with the wastewater and other mineral materials (approx. 60 l / 1000 m<sup>3</sup> of wastewater) from the digestible organic material.

Due to the significant organics content in the classified grit longitudinal grit traps are today additionally aerated to at least partly avoid settling of organic material in the grit trap and cause floating material (grease) to rise to the surface. According to Kalbskopf, aerated grit traps are generally laid out on the basis of the residence time of wastewater in the grit trap. However, even aerated grit traps are unable to ensure reliable separation of grit from organics. This can only be achieved by well performing grit washing plants.

- [HUBER Longitudinal Grit Trap ROTAMAT® Ro6](#)
- [HUBER Grit Trap GritWolf®](#)

## Downloads

 [Brochure: HUBER Longitudinal Grit Trap ROTAMAT® Ro6](#) [pdf, 309 KB]  
Further information

 [Brochure: HUBER Grit Trap GritWolf®](#) [pdf, 327 KB]  
Further information

## Case Studies

- [New HUBER Grit Trap GritWolf® setting new standards: Grit removal below 100 µm](#)

Winkelstrasse 12  
CH-6048 Horw

Telefon +41 (0)41 349 68 68  
Telefax +41 (0)41 349 68 78

E-mail: [info@picatech.ch](mailto:info@picatech.ch)  
[www.picatech.ch](http://www.picatech.ch)

MWST Nr. 156 391